



CBF Series Explosion-proof Axial Fan



Scope and use

1. This series of products is suitable for places with explosive gas mixtures (Zone 1 and 2) of H B class T4 and below groups, and is used for ventilation of workshops and warehouses or to strengthen heating, ventilation and heat dissipation.
2. The working conditions of this series of products are: AC 50Hz, voltage 220/380V without severe corrosion and significant dust.
3. This series of products can also add mounting brackets according to user requirements.
4. This series of products meet the requirements of explosion-proof mark Exd II BT4.

Name	Type	Wattage(kw)	Volume(m³/h)	Speed(r/min)	Voltage(V)	
Explosion-proof axial fan	CBF-200	0.09	1800	1450	220	380
	CBF-250	0.12	2000	1450	220	380
	CBF-300	0.18	2280	1450	220	380
	CBF-400	0.37	2880	1450	220	380
	CBF-500	0.55	5700	1450	220	380
	CBF-600	0.75	8700	1450	220	380
	CBF-700	1.1	10200	1450	/	380
	CBF-750	1.5	10500	1450	/	380



Type	ΦA	B	Φ1	Φ2	Blade diameter	Number of leaves	screw
200	249	266	212	232	195	4	1/2
250	302	269	264	284	238	4	1/2
300	355	277	305	329	285	4	1/2
400	454	276	405	433	390	3	1/2
500	556	298	506	533	490	3	3/4
600	655	298	606	633	590	3	3/4
700	764	402	708	740	685	3	3/4
750	806	402	748	781	740	3	3/4