




Stopping plug HPLG

Technical data

| | |
|---------------------------------|---|
| Marking according to 2014/34/EU |  II 2 GD Ex db IIC Gb  II 2 GD Ex eb IIC Gb  II 2 GD Ex tb IIIC Db |
| EC-Type Examination Certificate | DNV 22 ATEX 62580X |
| IECEx Certificate of Conformity | IECEx DNV 22.0091X |
| IECEx marking | Ex db IIC Gb Ex eb IIC Gb Ex tb IIIC Db |
| Type of protection | Ex d, Ex e, Ex t |
| Permissible ambient temperature | -55°C to +160°C |
| Protection rating | IP66 / IP68 (1.5 m, 2 h) |
| Material | Nickel plated brass*, stainless steel 316L, brass, electroless nickel plated* |

* - Available only on special order

Metric thread

| Thread | Ordering code |
|--------|---------------|
| M16 | HPLG 0M |
| M20 | HPLG 1M |
| M25 | HPLG 2M |
| M32 | HPLG 3M |
| M40 | HPLG 4M |
| M50 | HPLG 5M |
| M63 | HPLG 6M |
| M75 | HPLG 7M |
| M90 | HPLG 8M |

NPT thread

| Thread | Ordering code |
|--------|---------------|
| 3/8" | HPLG 0N |
| 1/2" | HPLG 1N |
| 3/4" | HPLG 2N |
| 1" | HPLG 3N |
| 1.1/4" | HPLG 4N |
| 1.1/2" | HPLG 5N |
| 2" | HPLG 6N |
| 2.1/2" | HPLG 6N |
| 3" | HPLG 8N |

Product coding

